

Simple, User Friendly Operation

Fully Featured :: Perfectly Priced

- ▶ USB Mouse Control
- ▶ Web Browser based
- ▶ Recording Rate: Max. 120ips (CIF)
- ▶ PTZ Control
- ▶ Motion Detection
- ▶ Jog/Shuttle Play Back



* Mouse not included

- ▶ Loop Through Video
- ▶ Ethernet 10/100 Base T
- ▶ Built In CD-RW and USB port
- ▶ Supports up to two internal hard drives
- ▶ Simultaneous video output VGA and Composite
- ▶ Triplex Operation (Monitoring/Playback/Recording)
- ▶ Audio Recording: 4 IN/1 OUT with two-way audio

GV-DVR1042

GV-DVR1042 | 4 CHANNEL STANDALONE DIGITAL VIDEO RECORDER



Video & Audio	Video Input	4
	Video Looping Out	4
	Live Resolution	120FPS
	Audio in / output	4 in / 1 output (RCA)
GUI	Resolution	704 X 480
	Control	Remote Control USB Mouse Front pannel manual control
		PTZ Control
Data Output	RS-485	
Monitor Outputs	Main Composite	1 (BNC)
	Spot Composite	1 (BNC)
	SVHS	1
	VGA	Yes
Recording & Playback	Compression Method	Modified MPEG 4
	Total Recording Speed	120 ips (CIF)
	Recording Speed / Each Individual Camera	30 ips
	Recording Video Resolution	352x240, 704x240, 704x480
	Fast Forward and Rewind Control	Yes(1x - 64x)
	Calendar & Event log search	Yes
	Jog/Shuttle Playback	Yes
Storage & Archiving	1 Internal Storage	2 HDD (No Limit in HDD Size) Available in 250 & 500Gb
	HDD TYPE	IDE
	CD-RW	1
	USB	USB Stick, USB CD/DVD-RW, USB HD
Alarm & Event	AVI File Format	ITX Software & WMP
	Input / Output	4 in / 1 output
	Alarm Notification	Buzzer, E-mail, Alarm camera to full screen
	Video Loss Detection	Yes
	Event Log	Yes
	Pre-alarm record	Up to 5 sec
	Post-alarm recording	3 minutes
Motion Event	S.M.A.R.T Alarm	Yes
	Motion Area Set	Full or partial area set up
	Motion Activity	12 x 12 Grid
	Motion Sensitivity	5 levels
	Multiple Motion	Yes
Network	Motion Pop Up	Yes
	Static & DHCP	Yes
	Networking access	View program & web via Internet
	Network Bandwidth Control	Yes
	Covert Channel	Yes
	Event Log Information via Remote Network Software	Yes
	Copy as JPEG, BMP	Yes
	Configurable multi-password protection	Yes
	Remote Monitoring	Yes
	Fast forward and rewind, playback and frame advance/rew	Yes
	Remote PTZ Control	Yes
	Multi User access to DVR system	Up to 4
	Alarm Pop-up at Remote client	Yes
Set up by Web Browser	Yes	
Client S/W requirements	Operating system	Windows XP
	Processor	Pentium 4 or better
	RAM Memory	256 MB or More
	VGA Model	RIVA TNT Pro 2 or More
	Service Pack	Windows XP (SP2)
	Internet Explorer	6.0 Ver or More
Environmental	Window Installer	Win XP (Ver 3.1)
	Dimensions (W x H x D)	14.4" x 2.6" x 14.4"(360 x 66 x 360mm)
	USB	Two ports for Storage and Archiving and Mouse
	Weight Approx.	15.4 lbs (7 kg)
Electrical	Temperature	41°F ~ 122°F (5° ~ 50°C)
	Humidity	10~90% RH non-condensing
	Power supply	Adaptor
	Input voltage	100~240V (12V) 5A by UL listed adaptor (supplied)
Certifications	Power Consumption	60W
	CE FCC	